

HELIX CLIP

CLEAN BREAK AT THE BASE OF THE CLIP



EVEN JOINT

Consistent joint width for a professional finish.



PERFECT LEVEL

Levels tiles quickly for a perfectly flat surface.




CLEAN BREAK

Clip snaps off at the base, leaving no residue in the joint.

TECHNICAL SPECIFICATIONS

Article	HELIX Levelling clip
Material	Pure polypropylene (PP)
Dimensions (L × W × H)	41.5 × 24 × 59.3 mm
Color	Natural
Joint width	1.5 - 2 - 3 - 4 mm
Tile thickness	3 - 17 mm
Packaging options	☒ 100 pcs ☒ 250 pcs ☒ 500 pcs
Compatible with	☒ HELIX cap ☒ Anti scratch disc

HOW TO USE IN 4 STEPS



1 APPLY ADHESIVE

Apply enough tile adhesive and place the first tile. Make sure it is perfectly level.



2 INSERT CLIPS

Slide the clip(s) under the tile and press the tile into the adhesive. Place the next tile on the base of the clip(s).



3 LEVEL THE TILES

Screw the cap onto the clip and tighten it firmly.



4 REMOVE THE CLIPS

Leave the cap in place. Once the tile adhesive has almost fully cured, remove the clip and cap with a rubber mallet in the direction of the joint.