

STARTER KIT

COMPLETE SET WITH CLIPS AND CAPS



EVEN JOINT

Consistent joint width for a professional finish.



PERFECT LEVEL

Levels tiles quickly for a perfectly flat surface.




CLEAN BREAK

Clip snaps off at the base, leaving no residue in the joint.

TECHNICAL SPECIFICATIONS

Item	HELIX Starter Kit
Contents	HELIX clips (200 pcs) HELIX caps (200 pcs)
Joint width	1.5 - 2 - 3 - 4 mm
Dimensions (L × W × H) HELIX Starter Kit	29 × 29 × 31.5 mm
Tile thickness	3 - 17 mm
Packaging	✓ 200 pcs ✓ 75 pcs
Compatible with	✓ Anti-scratch disc

HOW TO USE IN 4 STEPS



1

APPLY ADHESIVE

Apply enough tile adhesive and place the first tile. Make sure it is perfectly level.



2

INSERT CLIPS

Slide the clip(s) under the tile and press the tile into the adhesive. Place the next tile on the base of the clip(s).



3

LEVEL THE TILES

Screw the cap onto the clip and tighten it firmly.



4

REMOVE THE CLIPS

Leave the cap in place. Once the tile adhesive has almost fully cured, remove the clip and cap with a rubber mallet in the direction of the joint.